



AkzoNobel



DECLARATION OF PERFORMANCE

**In accordance with Annex III of Regulation (EU) No. 305/2011
(Construction Product Regulation)**

DoP_[UK]_445085287_1_001

1. Unique identification code of product-type:

Polycell Flexible Gap Polyfilla

2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):

Batch number: See product packaging

3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:

Sealants for façade elements
EN 15651-1: F-EXT-INT
CLASS 12,5P

4. Name, registered name or registered trade mark and contact address for the manufacturer as required to Article 11 (5):

ICI Paints AkzoNobel - Wexham Road - Slough SL2 5DS

5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
System 3 for reaction to fire

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 and reaction to fire under System 3 and issued: a test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: N/A



9. Declared performance:

Conditioning: Procedure A (according to ISO 8339)

Substrate: Mortar M2 (without primer)

Essential Characteristics	Performance	Harmonised Technical Standard
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	EN 15651-1:2012
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	EN 15651-1:2012
Loss of volume	≤ 25 %	EN 15651-1:2012
Tensile properties after immersion in water (at 23°C)	≥ 100 %	EN 15651-1:2012
Durability	Pass	EN 15651-1:2012

(*) See material safety data sheet

NPD: No Performance Determined

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by

Anita Drewes
Director Product Safety & Regulatory Affairs and Quality
AkzoNobel Decorative Paints

Sassenheim, 23 juni 2014



AkzoNobel



1213

ICI Paints AkzoNobel - Wexham Road - Slough SL2 5DS

14

CD_[UK]_445085287_1_001

Polycell Flexible Gap Polyfilla

EN 15651-1

Sealants for non-structural use in joints in buildings and pedestrian walkways.

Part 1: Sealants for facade elements for exterior and interior application.

Typ F-EXT-INT

CLASS 12,5P

Conditioning: Procedure A (according to ISO 8339)

Substrate: Mortar M2 (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 25 %	
Tensile properties after immersion in water (at 23°C)	≥ 100 %	
Durability	Pass	

(*) See material safety data sheet
NPD: No Performance Determined